

Amendments to the Specification including Abstract

There is no "New Material" in this amended specification. The original specification also included a double wall heat exchanger internal to the hot water tank in the Prior Art section of the last paragraph and in Figure 1. The related patent application, Internal Water Tank Solar Heat Exchanger has resulted in Patent US 6,837,303 B2.

The Abstract has been changed to be less than 150 words. It also more clearly states the subject invention as the use of a steam condensing pressurized radiator or pressure activated dampers to dissipate the solar collector heat, if fluid circulation stops; a fluid overflow/recovery system that keeps the fluid loop full of only liquid and steam, and eliminates all air.

Clean copy is first

Marked up copy second

United States Patent Application

Docket Number: 10/085,175

Dr. Barry Lynn Butler

Date of Filing: 2/27/2002

980 Santa Estella

Federal R&D: None

Solana Beach, California 92075

Assignment: None

SS# 156-34-3255

Related Applications: Internal Water
Tank Solar Heat Exchanger (US 6,837,303
B2)

**SOLAR HEAT TRANSFER SYSTEM (HTPL), High Temperature Pressurized
Loop**

BACKGROUND OF INVENTION

This invention pertains to the collection and the delivery of heat from a roof or a ground mounted solar collector panel to a hot water storage tank via the use of a self pressurized, higher temperature fluid filled loop, which eliminates non-condensable gases, such as air, from the fluid loop. The pressurized loop system utilizes a mixture of water and antifreeze or another suitable fluid is circulated via a pump. In addition, the system is self protected from over-temperature and over-pressure if the circulating pump fails. The higher temperature, compared to an un-pressurized, fluid heat transfer loop allows for a smaller heat transfer area and hence a more compact hot water tank heat exchanger, and a small diameter (approximately two inch), flexible, insulated umbilical which contains both electrical and fluid tubing connections (approximately 1/4 inch outside diameter tubing) to go both out and back from the hot water tank to the solar collector for ease of installation. This heat transfer loop system is unique since there are savings in materials for heat exchangers, piping, and insulation. The system also has built in air elimination, self protection from overheating and automatic system full of fluid maintenance.

PRIOR ART

Most common solar collector systems are either the un-pressurized or pressurized via an air bladder expansion tank and make use of a large area heat exchanger external to the water tank to exchange heat from the solar loop to the city water pressure in the hot water tank. Un-pressurized collector heat transfer loops are limited to the boiling point of the water/antifreeze mixtures, typically 50/50, at atmospheric pressure of approximately 220 ° Fahrenheit. A water/antifreeze mixture of approximately 50/50, pressurized to 14 PSI, or approximately two atmospheres in the collector loop, will not boil until 265 ° Fahrenheit. The higher operating temperature in the collector loop allows for efficient small area in the hot water tank heat exchangers to be utilized, which do not disturb the normal tank stratification. Internal tank heat exchanger also eliminates the pump that would circulate water from the hot water tank through the external heat exchanger. The stratification of the normal hot water tank, hot on top and cooler on the bottom, is disturbed by circulating water from the hot water storage tank, through the external heat exchanger. It is important not to disturb the normal tank stratification because it decreases the normal gas or electric heater efficiency.

Some solar collectors use pressurized drinking water and flow this water through the solar collector to heat it before it goes to the hot water tank inside the house. Other systems called integrated collector storage have a roof mounted hot water tank above the solar collectors filled with drinking water. The fresh potable water is subject to freezing and must be heated electrically at night to keep the roof mounted solar collector or integrated solar collector/hot water tank from freezing during cold weather. Other systems circulate potable water through the solar collectors only when they are illuminated by the sun, and must drain this water out at night during freezing weather. Drain down systems send the solar collector water down the drain, and get new fresh water the next day. Drain back systems have a holding tank that the solar collector water can drain into and be used over and over.

Main advantages: 1) Pressurized antifreeze heat transfer loops allow solar collectors and tank heat exchangers to operate up to 265 ° Fahrenheit; 2) Pressurized heat transfer loops allow heat to be transferred with very low fluid flow rates minimizing pumping power and allowing small diameter tubes to take fluid to and from the solar collector and water tank heat exchanger; 3) Keeping the fluid loop full of fluid and eliminating non-condensable air minimizes corrosion of the fluid loop containment walls; 4) Internal small area heat exchangers adapt to existing tanks with minimum re-plumbing and without tank removal or draining; 5) Heat exchanger is efficient; 6) Double wall heat exchanger safely separates toxic heat transfer fluids from potable water; 7) This solar system costs less to install and maintain; and 8) Solar system maintains normal tank stratification.

SUMMARY OF INVENTION

In summary, the present invention is a self pressurized, via fluid thermal expansion on heat system heat up, fluid filled and maintained full eliminating non-condensable air by the vacuum from fluid thermal and steam contraction, drawing fluid from the overflow reservoir back into the fluid loop, where heat is collected in a solar panel illuminated by the sun, heats a solution of water based antifreeze or other suitable liquid, the fluid is pumped at low flow rate to a hot water tank where it gives up the heat via a heat exchanger. The fluid loop is pressurized and can operate above the normal boiling point of water 212 ° Fahrenheit. The fluid loop also has a built in boiling and pressure activated over-temperature protection and over-pressure protection, so if the fluid circulation pump stops while the sun is shining the solar collector will not get too hot and damage itself, or make the heat transfer fluid more corrosive to the containment materials.

The primary objective of the present invention is to reduce the amount of material needed to collect and transport solar heat. This is accomplished by increasing the pressure and hence the temperature in the maintained full fluid loop, which decreases the

area of the hot water tank to fluid loop heat exchanger surface needed. The higher fluid temperature difference, between the hot water tank and the solar collector, allow more heat to be stored in each unit volume of fluid in the solar collector heat transfer loop. Hence a smaller volume of fluid, lower flow rate is needed to deliver the heat from the solar collector to the hot water tank. The higher fluid temperature in the collector will lower the collectors efficiency, since it is losing heat to the outside air. This loss is a small price to pay for a system using significantly less material.

Another objective is to reduce the time and complexity of retrofitting solar energy to existing homes, since it uses flexible small diameter tubing to carry the low fluid flow volume. The small diameter of the fluid carrying tubes, approximately $\frac{1}{4}$ inch outside diameter, also allows them to be thermally insulated and still be less than two inches in diameter. By adding an electrical wire bundle to the insulated fluid carrying tubes and wrapping them with a protective covering, an umbilical cord is created, which carries all fluids and electrical signals from the hot water tank to the solar collector. This plug and play umbilical allows for do-it-yourselfers or professionals to install the system more quickly. These fluid carrying tubes can be installed in existing buildings because they are flexible and can be fed into and through attics, walls and placed on the outside of buildings, without being unsightly.

Additional objectives, advantages and novel features of the invention will be set forth in the description which follows and will become apparent to those skilled in the art upon examination of the following. Others may be learned by practice of the invention. The objectives and advantages of the invention may be realized and attained by means of the instrumentalities and combinations particularly pointed out in the appended claims.

DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of the pressurized loop solar collector system, including the fluid loop, the solar collector, the hot water tank heat exchanger, the fluid pump, controller, the over-pressure relief and fluid full maintenance vacuum relief with overflow reservoir, and both boiling and pressure activated over-temperature systems.

FIG. 2 is a view of the boiling activated solar collector over-temperature system including the pressurized liquid-to-air radiator, the pressure relief valve and the fluid full maintenance system including the vacuum recovery valve and its external fluid reservoir.

FIG. 3 is a pressure activated solar collector over-temperature control system, which opens dampers in the collector to let heat out, when the fluid in the solar collector boils and raises and sustains the loop pressure to a point just below the regulated pressure.

FIG. 4 is a boiling activated solar collector over-temperature control system, which forces steam from the boiling solar collector into a pressurized liquid-to-air heat exchanger/radiator, which uses fins to reject heat from the radiator and condense the steam back to water, and then return this water to the main heat transfer loop.

FIG. 5 is a plot of solar collector air valve position versus pressure in the solar collector fluid loop.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The invention (FIG. 1) consists of a pressurized heat transfer loop (1, 14 & 17, which operates above the boiling point of water at one atmosphere of pressure, 212 ° Fahrenheit. The heat transfer fluid (13) is heated, in the solar collector tube (1) by the sun. The solar collector (2) can be single, or double glazed. The heated fluid then exits the solar collector in tube (1) and comes to a three-way connection. Path one (7) goes to the pressure actuator (6), which can move the actuator arm (5) to actuate air dampers with motion (4). Path one may not be needed if the path two pressurized fluid/steam-to-air radiator is sufficient to prevent overheating. Path two goes through a pressurized radiator (8) with fins (9) to a pressure relief valve (10) which includes a vacuum recovery valve to let expelled heat exchanger fluid (13) back into the system from the fluid overflow/recovery reservoir (12), while excluding non-condensable air. Path three (14) is

the fluid tubing leading to the hot water tank (22) heat exchanger (16). The insertable, internal heat exchanger is screwed into the tank through a tank port (24) and allows water tank fluid (30) ingress or egress via a side port (26). The inside of the outer heat exchanger wall (16) is in physical contact with the outside of tubes (14 & 17). Physical contact means that over a significant area or approximately 50% of the surfaces, the interfaces are compressed together mechanically so heat can cross the interface, but leaking liquid from either side will move along the interface. The tube (14) turns around in the bottom of the heat exchanger and becomes the tube (17) exiting the heat exchanger. The tubes (14 & 17) are much hotter than the water in the hot water tank (30) and are in physical contact with the wall (16) so the heat is transferred from the heat transfer fluid (13) through the first wall (14 or 17) then through the mechanical interface to the second wall (16) then into the water (30). Once the tube (17) leaves the heat exchanger it returns to the pump (20) inlet. The tube (17) then returns to the solar collector tube (1) for the heating of the fluid (13).

To transport the pressurized fluid and the heat it contains from the solar collector to the hot water heater a flexible insulated umbilical is used (15). The umbilical consists of thermally insulated fluid connections (14 & 17) from the solar collector (1 & 2) to the hot water tank, rubber closed-cell thermal insulation (32), the low voltage electrical connections and a weather resistant covering of polymer pipe (31), the two small diameter tubes (14 & 17) containing the solar collector heated fluid (13). This allows the two-tube bundle to be flexible and insulated (32) and still be less than 2 inches in diameter. The small copper tubes are connected together with standard tubing unions, angles and T-connectors of about 1/4, 5/16, or 3/8 inch tube size.

The solar collector (2), an integral part of the collector, is a set of dampers which are opened by pressure (15). These dampers are only open when the solar heat collected is more than the hot water tank can use. These dampers when opened allow outside air of less than 120 ° Fahrenheit to flow over the absorber plate, where the sunlight is converted to heat and transferred into the heat transfer fluid. This airflow cools the absorber and stops the boiling. Then the dampers close and the absorber heats back up. The dampers open and close on a two to five minute cycle and only minor boiling is allowed to take place. This self-controlling feature is unique and allows the collector to protect itself,

even if the fluid flow in the pressurized loop (1, 14 & 17) stops. Alternatively to the dampers, or along with them, one could use the boiling activated radiator system shown in (FIG. 1, 2 & 4,) which is a pressurized side channel to the main pressurized heat transfer loop, which is at the uppermost point in the main fluid loop. As steam bubbles form in the solar collector they try to escape by going into the side channel heat exchanger. The fluid there is below the boiling point of the pressurized fluid and they collapse and condense. The fluid in the side channel is cooler because the outer surface is exposed to the outside air via fins (9). If no bubbles are forming in the solar collector, then there is no flow of fluid in the side channel and the fluid in the side channel stays cool.

The system has two possible configurations for activating the heat transfer fluid pump (20). The first is a conventional control system run by household 115VAC power. This control system has a control box (52), which plugs into the wall outlet and has two sensors. The collector has a temperature sensor using low voltage (50), where the electrical wires are part of the umbilical to tell the controller, which turns on the pump, when the solar collector temperature exceeds the hot water tank temperature, which is measured by sensor (56) on the hot water tank. The sensor (56) is usually placed near the top of the tank (22), which tells the controller when the tank is getting too hot, i.e. no one home to use hot water, then the controller will shut off the pump. This would now cause the pressure damper or side channel heat exchanger to protect the collector from excessive boiling, which would block the collector tubes with mineral deposits over time.

The second pumping system is based on using a photovoltaic array (60), which provides 12 Volt power when the sun is shining. This power is carried down to the pump on the umbilical connector wire. The pump is a DC powered pump, which is capable of low flow at modest pressures. A control box may not be necessary. When the sun is out the pump pumps, when it is not, the pump stops. A thermal disconnection switch (64), is placed on the top of the hot water tank, so if the hot water tank gets too hot, it will disconnect the pump.

The invention also consists of a pressurized radiator, pressure relief and vacuum recovery valve, and fluid overflow recovery system (Fig. 2). This system includes: a

pressurized fluid radiator (8) with fins (9) to conduct heat from the fluid to the surrounding air; a reservoir (12); a pressure cap (10) to regulate the pressure in the system; a vacuum relief valve to allow the overflowed fluid to return to the system upon cool down at night via the vacuum relief valve (18) which is built into pressure cap (10); a fluid overflow and recovery reservoir (12) to the pressure relief (10) and vacuum recovery (18) valves via tube (72) while excluding non-condensable air, since tube (72) enters the fluid (13) below the surface level. The pressure of the fluid in the solar collector heat transfer loop is regulated by the pressure cap, which uses a spring (15) to push against the fluid pressure over a fixed area. During normal daily operation when the sun is out, the heat transfer fluid (13) expands as it heats from 75 ° Fahrenheit to over 230° Fahrenheit. When the pressure reaches the set pressure, i.e. 16 PSIG, fluid and any trapped air is pushed out past pressure relief valve (10) and overflows to the fluid overflow reservoir (12) via tube (72). In the overflow reservoir (12) the fluid is retained and the air bubbles move from the bottom of tube (72) which is below the liquid surface to the liquid surface, burst and are vented to the atmosphere by a cap (70). At night, when the fluid and condensable steam in the solar heat transfer system cools and contracts, fluid only is drawn back through vacuum relief valve (18), by the vacuum in the fluid loop caused by fluid contraction. The vacuum relief pressure is set by spring (16) to about minus two PSIG, into the heat transfer system to keep it full of fluid and keep non-condensable air out. Air in the system increases the corrosion of the fluid loop. This simple system allows the approximately 50% water/50% antifreeze mixture in the solar heat transfer loop to heat up to over 212 ° Fahrenheit, without boiling until it reaches almost 265 ° Fahrenheit, at 16 PSIG confinement pressure. This higher temperature allows for heat to be transferred more efficiently into the hot water tank, using lower flow rates and a small surface area internal (or external) hot water tank heat exchanger.

The invention also consists of a pressure activated solar collector over-temperature protection system (Fig 3). An integral part of the collector is a set of dampers (86 & 88) on both the top and bottom of the solar collectors, which are opened by pressure actuator (6). These dampers are only open when the solar heat collected is more than the hot water tank can use and the solar collector begins to boil. These

dampers, when opened, allow outside air of less than 120 ° Fahrenheit to flow over the absorber plate (FIG. 1 (3)), where the sunlight is converted to heat and transferred into the heat transfer fluid. This airflow cools the absorber and stops the boiling. Then the dampers close and the absorber heats back up. The dampers open and close on a two to five minute cycle and only minor boiling is allowed to take place. This self-controlling feature is unique and allows the collector to protect itself, even if the fluid flow in the pressurized loop (FIG. 1. tubes 1, 14 & 17) stops.

The pressure activated control system is needed if fluid circulation stops for any reason while the sun is shining, i.e. controller turns off pump, or pump failure, or power failure, or fluid loop blockage. The pressure activated system consists of a solar system fluid pressure-activated actuator (6), such as a piston (84), or other pressure-activated actuator, which is in a retracted state at normal system operating pressure and in an extended state at the pressure cap relief setting, such as 16 PSIG. A spring (82) or a pressurized cavity can be used to return the actuator to the retracted state, when the solar system pressure falls to normal operating pressure. The solar system fluid (13) is sealed into the system via a bellows (80) or another acceptable seal, such as an O-ring. The actuator is connected to the fluid loop (7). This actuator output (5) is connected via linkage (4) to a hinged or a sliding valve (86, 88), like a furnace damper, which allows air to flow over the solar collector absorber plate (Fig. 1. (1)) and cool it off with outside air. Over-temperature protection is achieved by successive airflow movements over the solar collector absorber plate. When the solar collector gets too hot the heat transfer fluid (13) boils in the solar collector. This causes the pressure actuator to extend and open the collector air damper valves into position (91), opening up holes (90) for air movement over the solar collector absorber plate (Fig. 1. (1)), which takes the heat out of the solar collector and the heat transfer fluid temperature drops below the boiling point and stops boiling. When the system pressure returns to normal, the actuator retracts and closes the solar collector air damper valves into position (92). This air valve open/close cycle repeats itself until the sun goes down, or until the fluid flow is reestablished. Thus the collector prevents damage to the system by keeping the collector near the pressurized boiling point of the water/antifreeze mixture under non-circulation conditions. Non-circulation can occur normally if the hot water tank is hot enough and the controller shuts

off the pump and abnormally if the pump fails, power fails or the fluid flow path is blocked.

The invention also consists of a boiling activated solar collector over-temperature protection system (FIG. 4). The system consists of a pressurized liquid-to-air-radiator heat exchanger, and a boiling gas, steam/liquid, separator. During normal operation, the entire system is full of heat transfer fluid (13) and no boiling occurs. The liquid-to-air heat exchanger (8) with fins (9) is a side arm and usually has no fluid flow in it. Normally the fluid flows into the boiling gas separator (94) from the solar collector tube (1) and out of the boiling gas separator down tube (14) to the hot water tank (22). Under non-flow conditions, such as circulating pump failure or the solar input being greater than the hot water tank can use, the solar collector (2) will begin to boil. In this event, the boiling gas separator (94) allows the gas (steam) bubbles to go up by buoyancy into the liquid-to-air heat exchanger (8), which stirs the liquid in the heat exchanger, while condensing the boiling gas back to a liquid, and heats the heat exchange fins (9) above the outside air temperature and dissipates this heat from the pressurized liquid (13) in heat exchanger (8) to the outside air. The filler tube (92) allows condensed pressurized liquid to come from the liquid-to-air exchanger and be inserted below where the gas (steam) bubbles are being released tube (1) into the boiling gas separator (94) keeping the collector fluid loop (14 & 17) full of liquid, while liquid and gas, steam, exist in the collector (1). The water based heat pipe system allows a small amount of boiling in the solar collector to take place; the generated steam travels up by buoyancy to the pressurized heat exchanger, which rejects heat to the atmosphere via the pressurized liquid (8) to the air radiator (9) heat exchanger. As long as solar collector boiling takes place, the pressurized liquid in the side arm heat exchanger (8) will be heated by condensing of the steam. Non-condensable air in the boiling solar collector will impede the flow of steam to the pressurized heat exchanger, so air must be kept out of the system. Only a small amount of fluid will be forced into a fluid overflow tube (72) into atmospheric reservoir (12). The advantage of this system over, the pressure activated solar collector air vents, is that boiling activated heat pipe system has fewer moving parts and can easily dissipate all of the heat that the solar collector can gather from the sun, without pump power circulation of the heat exchange fluid..

The graph in FIG. 5 shows the actuator and air valve position as a function of system pressure. The air valves (Fig. 3 (90)) are in the shut position (Fig. 3 (92)) and the actuator retracted until a pressure of approximately 80% (102) of the system pressure, maintained by the pressure relief valve (Fig. 4. (10)) is reached. At pressures above (102) the air valves begin to open and are fully open by the time the system reaches 95% (104) of the system pressure maintained by the pressure relief valve. This arrangement allows the system to cool itself before vigorous boiling occurs. The pressure versus actuator position profile is determined by the piston area (Fig.3. (84)) and spring constant (Fig. 3. (82)).

ABSTRACT

Delivering heat from modern high temperature solar collectors to hot water storage tanks is more effectively done using a self pressurized, automatic air eliminating, higher temperature fluid loops. A pressurizing valve, an overflow reservoir and a vacuum relief valve are used. Non-toxic water/antifreeze mixtures are pressurized up to about two atmospheres resulting in a 265 ° Fahrenheit boiling point. Loss of circulation under full sun results in solar collector boiling under pressure. A steam heat pipe is set up between the solar collector and the pressurized liquid-to-outside-air-radiator. The steam generated in the solar collector is condensed in the liquid-to-air-radiator and returned to the solar collector to keep it completely full of fluid and steam. A set of pressure activated air dampers on the solar collector can also be used to shed the excess solar collector heat.

United States Patent Application

Docket Number: 10/085,175

Dr. Barry Lynn Butler

Date of Filing: 2/27/2002

980 Santa Estella

Federal R&D: None

Solana Beach, California 92075

Assignment: None

SS# 156-34-3255

Related Applications: Internal Water

Tank Solar Heat Exchanger (US 6,837,303

B2)

**SOLAR HEAT TRANSFER SYSTEM (HTPL), High Temperature Pressurized
Loop**

BACKGROUND OF INVENTION

This invention pertains to the collection and the delivery of heat from a roof or a ground-mounted solar collector panel to a hot water storage tank via the use of a self pressurized, higher temperature fluid filled loop, which eliminates non-condensable gases, such as air, from the fluid loop. The pressurized loop system utilizes a mixture of water and antifreeze mixture or another suitable fluid is circulated via a pump. In addition, the system is self protected from over-temperature and over-pressure if the circulating pump fails. The higher temperature, compared to an un-pressurized, fluid heat transfer loop allows for a smaller heat transfer area and hence a more compact, hot water tank heat exchanger, and a small diameter, (approximately 2-two inch-inch), diameter, flexible, insulated umbilical which containing contains both electrical and fluid tubing connections, (approximately 1/4 inch-outsideinch outside diameter tubing,) to go to and both out and back from the hot water tank to the solar collector for ease of installation. This heat transfer loop system is unique ~~since there are~~ savings in materials for heat exchangers, piping, insulation and insulation, and the ~~The system also~~

has built in air elimination, self protection from overheating, and automatic system full of
makefluid maintenance this collector system unique.

PRIOR ART

Most common solar collector systems are either the un-pressurized or pressurized
via an air bladder expansion tank and make use of a large area heat exchanger external to
the water tank to exchange heat from the ~~un-pressurized~~ solar loop to the city water
pressure in the hot water tank. Un-pressurized collector heat transfer loops are limited to
the boiling point of the water-water/antifreeze mixtures, typically 50/50, at atmospheric
pressure of approximately 220 o -degrees Fahrenheit. A ~~water-water~~ antifreeze mixture
of approximately 50/50, pressurized to ~~fourteen~~ 14 PSI, or approximately two
atmospheres in the collector loop, will not boil until 265 -degrees-o Fahrenheit. The
higher operating temperature in the collector loop allows for efficient small area in the
hot water tank heat exchangers to be utilized, which do not disturb the normal tank
stratification. Internal tank heat exchanger also eliminates the pump that would circulate
water from the hot water tank through the external heat exchanger. The stratification of
the normal hot water tank, hot on top and cooler on the bottom, is disturbed by circulating
water from the hot water storage tank, through the external heat exchanger. It is
important not to disturb the normal tank stratification, because it decreases the normal gas
or electric heater efficiency.

Some solar collectors use ~~City line water~~ pressureized drinking water and flow
this ~~city~~ water through the solar collector to heat it before it goes to the hot water tank
inside the house. ~~These systems~~ Other systems are called integrated collector storage;
have a roof mounted hot water tank above the solar collectors filled with drinking
water systems. The ~~city~~ fresh potable water is subject to freezing and must be heated
electrically at night to keep the roof mounted solar collector or integrated solar
collector/hot water tank from freezing during cold weather. ~~Other systems,~~ systems
~~which~~ circulate potable water through the solar collectors only when ~~they're~~ they are

illuminated by the sun, and must drain this water out at night during freezing weather.
Drain down systems send the solar collector water down the drain, and get new fresh
water the next day. Drain back systems have a holding tank that the solar collector water
can drain into and be used over and over.

Main advantages: 1) Pressurized antifreeze heat transfer loops ~~Allows-allow~~ solar collectors and tank heat exchangers to operate up to 265 ~~o-degrees~~ Fahrenheit; 2) Pressurized heat transfer loops allows heat to be transferred with very low fluid flow rates minimizing pumping power and allowing small diameter tubes to take fluid to and from the solar collector and water tank heat exchanger; 3) Keeping the fluid loop full of fluid and eliminating non-condensable air minimizes corrosion of the fluid loop containment walls; 4) Internal small area heat exchangers adapts to existing tanks with minimum re-plumbing and without tank removal or draining; 25) Heat exchanger is efficient; 36) Double wall heat exchanger safely separates toxic heat transfer fluids from potable water; 47) This solar system costs less to install and maintain; and 58) Solar system maintains normal tank stratification.

SUMMARY OF INVENTION

In summary, the present invention is a self ~~Pressurized~~-pressurized, via fluid thermal expansion on heat system heat up, fluid filled and maintained full eliminating non-condensable air by the vacuum from fluid thermal and steam contraction, drawing fluid from the overflow reservoir back into the fluid loop, where heat is collected in a solar panel illuminated by the sun, heats a solution of water based antifreeze or other suitable liquid, the fluid is pumped at low flow rate to a hot water tank where it gives up the heat via ~~an internal~~ heat exchanger. The fluid loop is pressurized and can operates above the normal boiling point of water 212° Fahrenheit. The fluid loop also has a built in boiling and pressure activated over-temperature protection and over-pressure protection-built in, so if the fluid circulation pump stops, while the sun is shining that the

system-solar collector will not get too hot and damage itself, or make the heat transfer fluid more corrosive to the containment materials.

The primary objective of the present invention is to reduce the amount of material needed to collect and transport solar heat. This is accomplished by increasing the pressure and hence the temperature in the maintained full fluid loop, which decreases the area of the hot water tank to fluid loop heat exchanger surface needed. The higher fluid temperature difference, between the hot water tank and the solar collector, allow more heat to be stored in each unit volume of fluid in the solar collector heat transfer loop. Hence a smaller volume of fluid, lower flow ~~rate~~, rate is needed to deliver the heat from the solar collector to the hot water tank. The higher fluid temperature in the collector will lower the collectors efficiency, since it is loosing heat to the outside air. This loss is a small price to pay for a system using significantly less material.

Another objective is to reduce the time and complexity of retrofitting solar energy to existing homes, since it uses flexible small diameter tubing to carry the low fluid flow volume. The small diameter of the fluid carrying tubes, approximately $\frac{1}{4}$ ~~the~~ inch outside diameter, also allows them to be thermally insulated and still be less than 2-two inches in diameter. By adding an electrical wire bundle to the insulated fluid carrying tubes and wrapping them with a protective covering, an umbilical cord is created, which carries all fluids and electrical signals from the hot water tank to the solar collector. This plug and play umbilical allows for do-it-yourselfers or professionals to install the system more quickly. These fluid carrying tubes can be installed in existing buildings, because they are flexible and can be fed into and through attics, walls and placed on the outside of buildings, without being unsightly.

Additional objectives, advantages and novel features of the invention will be set forth ~~in-part~~ in the description which follows and ~~in-part~~ will become apparent to those skilled in the art upon examination of the following. Others may be learned by practice of the invention. The objectives and advantages of the invention may be realized and attained by means of the instrumentalities and combinations particularly pointed out in the appended claims.

DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of the pressurized loop solar collector system, including the fluid loop, the solar collector, the hot water tank heat exchanger, the fluid pump ~~and~~, controller ~~and~~, the over-pressure relief and fluid full maintenance vacuum relief with overflow reservoir, and both boiling and pressure activated over-temperature systems.

FIG. 2 is a view of the boiling activated solar collector over-pressure-temperature system ~~and including the pressurized liquid-to-air radiator, the pressure relief valve and the fluid full maintenance system including the vacuum recovery valve and its associated fluid recovery system, with the external fluid recovery system reservoir.~~

FIG. 3 is a pressure activated solar collector over-temperature control system, which opens dampers in the collector to let heat out, when the fluid in the ~~loop solar collector~~ boils and raises and sustains the loop pressure to a point just below the regulated pressure.

FIG. 4 is a boiling activated solar collector over-temperature control system, which forces fluid-steam from the ~~main fluid loop~~ boiling solar collector into a pressurized liquid-to-air heat exchanger-/radiator, to, which uses fins to let heat out of reject heat from the fluid radiator loop and condense the steam back to water, when the fluid in the loop boils and then return this water to the main heat transfer loop.

FIG. 5 is a plot of solar collector air valve position versus pressure in the solar collector fluid loop.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The invention (FIG. 1) consists of a pressurized heat transfer loop (1, 14 & 17, which operates ~~well~~ above the boiling point of water at one atmosphere of pressure, 212

^odegrees Fahrenheit (FIG. 1). The water-heat transfer fluid (13) is heated, in the solar collector tube (1) by the sun,-. The solar collector (2) can be in-the single, or double glazed,-. The heated fluid then exits the solar collector in tube (1) and comes to a three-way connection. Path one (7) goes to the pressure actuator (6), which can move the actuator arm (5) to actuate air dampers with motion (4). Path one may not be needed if the path two pressurized fluid/steam-to-air radiator is sufficient to prevent overheating. Path two goes through a pressurized radiator (8) with fins (9) to a pressure relief valve (10) which includes a vacuum recovery valve to let expelled heat exchanger fluid (13) back into the system from the fluid overflow/recovery reservoir (12), while excluding non-condensable air. Path three (14) is the fluid tubing leading to the hot water tank (22) heat exchanger (16). The insertable, internal heat exchanger is screwed into the tank through a tank port (24) and allows water tank fluid (30) ingress or egress via a side port (26). The inside of the outer heat exchanger wall (16) is in physical contact with the outside of tubes (14 & 17). Physical contact means that over a significant area or approximately 50% of the surfaces, the interfaces are compressed together mechanically so heat can cross the interface, but leaking liquid from either side will move along the interface. The tube (14) turns around in the bottom of the heat exchanger and becomes the tube (17) exiting the heat exchanger. The tubes (14 & 17) are much hotter than the water in the hot water tank (30) and are in physical contact with the wall (16) so the heat is transferred from the heat transfer fluid (13) through the first wall (14 or 17) then through the mechanical interface to the second wall (16) then into the water (30). Once the tube (17) leaves the heat exchanger it returns to the pump (20) inlet. The tube (17) then returns to the solar collector tube (1) for the heating of the fluid (13).

To transport the pressurized fluid and the heat it contains from the solar collector to the hot water heater a flexible insulated umbilical is used (15). The umbilical consists of thermally insulated fluid connections (14 & 17) from the solar collector (1 & 2) to the hot water tank, rubber closed-cell thermal insulation (32), the low voltage electrical connections and a weather resistant covering of polymer pipe (31), the two small diameter tubes (14 & 17) containing the solar collector heated fluid (13). This allows the two-tube bundle to be flexible and insulated (32) and still be less than 2 inches in

diameter. The small copper tubes are connected together with standard tubing unions, angles and T-connectors of about 1/4, 5/16, or 3/8 inch tube size.

The solar collector (42), an integral part of the collector, is a set of dampers, which are opened by pressure (15). These dampers are only open when the solar heat collected is more than the hot water tank can use. These dampers when opened allow outside air of less than 120 ^o degrees Fahrenheit to flow over the absorber plate, where the sunlight is converted to heat and transferred into the heat transfer fluid. This airflow cools the absorber and stops the boiling. Then the dampers close and the absorber heats back up. The dampers open and close on a 2-two to 5-five minute cycle and only minor boiling is allowed to take place. This self-controlling feature is unique and allows the collector to protect it-self, even if the fluid flow in the pressurized loop (1, 14 & 17) stops. Alternatively to the dampers, or along with them, one could use the boiling activated radiator system shown in (FigFIG. 1, 2 & 4, (29)), which is a pressurized side channel to the main pressurized heat transfer loop, which is at the uppermost point in the main fluid loop. As gas-steam bubbles form in the solar collector they try to escape by going into the side channel heat exchanger. The fluid there is below the boiling point of the pressurized fluid and they collapse and condense. The fluid ~~is-in~~ the side channel is cooler, because the outer surface is exposed to the outside air via fins (9). If no bubbles are forming in the solar collector, then there is no flow of fluid in the side channel and the fluid in the side channel stays cool.

The system has two possible configurations for activating the heat transfer fluid pump (4220). The first is a conventional control system run ~~from-by~~ household 115VAC power. This control system has a control box (4452), which plugs into the wall outlet and has ~~three-two~~ sensors. The collector has a temperature sensor using low voltage (850), ~~who's-where the electrical-wire~~ electrical wires are part of the umbilical, to tell the controller, which turns on the pump, when the solar collector temperature exceeds the hot water tank temperature, which is measured by sensor (4056) ~~at the bottom of on~~ the hot water tank. ~~There is also a sensor~~ The sensor in (56) is usually placed near the top of the tank (922), which tells the controller when the tank is getting too hot, i.e. no one home to use hot water, then the controller will shut off the pump. This would now cause the pressure damper or side channel heat exchanger to protect the collector from excessive

boiling, which ~~will~~ would block the collector tubes with ~~seale~~ mineral deposits in over time.

The second pumping system is based on using a photovoltaic array (60), which provides 12 Volt power when the sun is shining. This power is carried down to the pump on the umbilical connector wire. The pump is a DC powered pump, which is capable of low flow at modest pressures. ~~There is no~~ A control box may not be necessary. When the sun is out the pump pumps, when it is not, the pump stops. A thermal disconnection switch (1864), is placed on the top of the hot water tank, so if ~~it~~ the hot water tank gets too hot, it will disconnect the pump.

~~The internal tank heat exchanger adapter (13), screws into the inlet or outlet port of the hot water tank (14) the house water to be heated now exits or enters the tank now via a side arm of the adapter. The pressurized loop heat exchanger fluid enters and exits the adapter in small diameter copper tubing, like quarter inch outside diameter copper tubing.~~

~~To transport the pressurized fluid and the heat it contains from the solar collector to the hot water heater and flexible insulated umbilical is used (7). The umbilical consists of the thermally insulate fluid connections and the low voltage electrical connections in one easy to run length. The two small diameter copper tubes, hot collector fluid to the hot water tank and cooler fluid returning from the hot water tank to the collector, are held apart by a spacer, such as a polymer coating applied to each, so the can be placed next to each other without touching and tied together along their length. This allows the two tube bundle to be flexible and insulated with a 3/4 inch thick insulating jacket and still be less than 2 inches in diameter. Adding a wire cable to the outside of the umbilical allows sensor (8) to be easily connected to the controller. The small diameter copper tubes are connected together with standard 1/4, 5/16, or 3/8 unions and T connectors (5).~~

_____ The invention also consists of a pressurized radiator, pressure relief and vacuum recovery valve, and fluid overflow recovery system (Fig. 2). ~~and~~ This system includes: a pressurized fluid radiator (8) with fins (9) to conduct heat from the fluid to the surrounding air; a reservoir (312); a pressure cap (10) to regulate the pressure in the system; ~~and;~~ a vacuum relief valve to allow the overflowed fluid to return on to the

system upon cool down at night via the vacuum relief valve (218) which is built into pressure cap (10); ~~which is connected to~~ a fluid overflow and recovery reservoir (412) to the pressure relief (10) and vacuum recovery (18) valves via tube (72) while excluding non-condensable air, since tube (72) enters the fluid (13) below the surface level. The pressure of the fluid in the solar collector heat transfer loop is regulated by the pressure cap, which uses a spring (15) to push against the fluid pressure over a fixed area. During normal daily operation when the sun is out, the heat transfer fluid (13) expands as it heats from 75 °degrees Fahrenheit to over 230-°degrees Fahrenheit, ~~and w~~When the pressure reaches the set pressure, i.e. 16 PSIG, fluid and any trapped air is pushed out past pressure relief valve (10) and overflows to the fluid overflow reservoir (2412) via tube (72). In the overflow reservoir (12), the fluid is retained and the air bubbles move from the bottom of tube (72) which is below the liquid surface to the liquid surface, burst and are ~~which is~~ vented to the atmosphere by a cap (3070). At night, when the fluid and condensable steam in the solar heat transfer system cools and contracts, fluid only is drawn back through vacuum relief valve (18), by the vacuum in the fluid loop caused by fluid contraction. The vacuum relief pressure is set by spring (16) to about minus two PSIG, into the heat transfer system to keep if it full of fluid and keep non-condensable air out. Air in the system increases the corrosion of the fluid loop. This simple system allows the approximately 50% water/-50% antifreeze mixture in the solar heat transfer loop to heat up to over 212 °degrees Fahrenheit, without boiling until it reaches almost 265 °degrees Fahrenheit, at 16 PSIG confinement pressure. This higher temperature allows for heat to be transferred more efficiently into the hot water tank, using lower flow rates and ~~an a~~ a small surface area internal (or external) hot water tank heat exchanger.


The invention also consists of a pressure activated solar collector over-temperature protection system (Fig 3). An integral part of the collector is a set of dampers (86 & 88) on both the top and bottom of the solar collectors, which are opened by pressure actuator (456). These dampers are only open when the solar heat collected is more than the hot water tank can use and the solar collector begins to boil. These dampers, when opened, allow outside air of less than 120 °degrees Fahrenheit to flow over the absorber plate (FIG. 1 (3)), where the sunlight is converted to heat and

transferred into the heat transfer fluid. This airflow cools the absorber and stops the boiling. Then the dampers close and the absorber heats back up. The dampers open and close on a 2-two to 5-five minute cycle and only minor boiling is allowed to take place. This self-controlling feature is unique and allows the collector to protect it-self, even if the fluid flow in the pressurized loop (FIG. 1. tubes 1, 14 & 17) stops. |

The pressure activated control system is needed if fluid circulation stops for any reason while the sun is shining, i.e. controller turns off pump, or pump failure, or power failure, or fluid loop blockage. The pressure activated ~~This~~-system consists of a solar system fluid pressure-activated actuator (46), such as a piston (2284), or other pressure-activated actuator, which is in a retracted state at ~~atmospheric~~-normal system operating pressure and in an extended state at the pressure cap relief setting, such as 16 PSIG. A spring (2082) or a pressurized cavity can be used to return the actuator to the retracted state, when the solar system pressure falls to ~~atmospheric~~-normal operating pressure. The solar system fluid (2413) is sealed into the system via a bellows (2380) or another acceptable seal, such as an O-ring. The actuator is connected to the fluid loop (47).

This actuator output (245) is connected via linkage (4) to a hinged or a sliding valve (2586, 2688), like a furnace damper, which allows air to flow over the solar collector absorber plate (Fig. 1. (1)) and cool it off with outside air. Over-temperature protection is achieved by successive airflow ~~events~~-movements over the solar collector absorber plate. When the solar collector gets too hot the heat transfer fluid (2413) boils in the solar collector. This causes the pressure actuator to extend and open ~~to the~~ collector air damper valves into position (91), opening up holes (90) for air movement over the solar collector absorber plate (Fig. 1. (1)), which takes the heat out of the solar collector and the heat transfer fluid temperature drops below the boiling point and stops boiling. ~~The~~ When the system pressure returns to ~~atmospheric~~-normal, ~~and the~~ actuator retracts and closes the solar collector air damper valves into position (92). This air valve open/close cycle repeats itself until the sun goes down, or until the fluid flow is reestablished. Thus the collector prevents damage to the system, by keeping the collector near the pressurized boiling point of the water/antifreeze mixture, under non-circulation conditions. Non-circulation can occur normally if the hot water tank is hot enough and the controller shuts

~~off the pump, and abnormally if the pump fails to circulate the heat transfer fluid, power fails or the fluid flow path is blocked. The inset in Figure 3 shows that the actuator and air valve position as a function of system pressure. The air valves are shut and the actuator retracted until a pressure of approximately 80% of the system pressure, maintained by the pressure cap is reached. Their air valves are open and the actuator extended by the time the system reaches 95% of the system pressure maintained by "the radiator cap". This arrangement allows the system to cool itself before vigorous boiling occurs. The pressure vs. actuator position profile is determined by the piston area (22) and spring (20) constant.~~



_____ The invention also consists of a boiling activated solar collector over-temperature protection system (Fig-FIG. 4). The system consists of a pressurized liquid-liquid-to-to-air-radiator heat exchanger, and a boiling gas, steam/liquid-separator, separator. During normal operation, the entire system is full of heat transfer fluid (2113) and no boiling occurs. The liquid-liquid-to-to-air heat exchanger (298) with fins (9) is a side arm and normally-usually has no fluid flow in it. Normally the fluid flows into the boiling gas separator (94) from the solar collector tube (1) and out of it-the boiling gas separator down tube (14) to the hot water tank (22). Under ~~abnormal-non-flow~~ conditions, such as circulating pump failure or the solar input being greater than the hot water tank can use, the solar collector (2) will begin to boil. In this event, the boiling gas separator (2894) allows the gas (steam) bubbles to go up by buoyancy into the liquid-liquid-to-to-air heat exchanger (298), which stirs the liquid in the heat exchanger, while condensing the boiling gas back to a liquid, and heats it-the heat exchange fins (9above) above the outside air temperature and dissipates this heat from the pressurized liquid (13) in heat exchanger (8) to the outside air. The filler tube (2792) allows condensed pressurized liquid to come from the liquid-to-air exchanger and be inserted below where the gas (steam) bubbles are being released tube (1) into the boiling gas separator (2894) keeping the collector fluid loop (14 & 17) full of liquid, while liquid and gas, steam, exist in the collector (1) -

The water based heat pipe system allows a small amount of boiling in the solar collector to take place, place; the generated steam travels up by buoyancy to the pressurized heat

exchanger, which rejects heat to the atmosphere via the pressurized liquid (8) to the their
air radiator (9) heat exchanger. As long as solar collector boiling takes place, the
pressurized liquid in the side arm heat exchanger (8) will be heated by condensing of the
boiling gassteam. Non-condensable air in the boiling solar collector will impede the flow
of steam to the pressurized heat exchanger, so air must be kept out of the system. Only a
small amount a-of fluid will be forced into a fluid overflow tube (72) steam-condenserinto
atmospheric (reservoir (412)). The advantage of this system over, the pressure activated
solar collector air ventsis, is that it-boiling activated heat pipe system has no fewer
moving parts and can easily dissipate all of the heat that the solar collector can gather
from the sun, without pump power circulation of the heat exchange fluid.

The inset-graph in Figure-FIG. 3-5 shows that-the actuator and air valve position
as a function of system pressure. The air valves- (Fig. 3 (90)) are in the shut position
(Fig. 3 (92)) and the actuator retracted until a pressure of approximately 80% (102) of the
system pressure, maintained by the pressure eaprelief valve (Fig. 4. (10)) is reached.
Their-At pressures above (102) the air valves are-begin to open and the-actuator extended
are fully open by the time the system reaches 95% (104) of the system pressure
maintained by _"the radiator-pressure eap"-relief valve. This arrangement allows the
system to cool itself before vigorous boiling occurs. The pressure vs-ersus actuator
position profile is determined by the piston area (22Fig.3. (84)) and spring constant
(20Fig. 3. (82))-constant.

3